





The HEAVY-DUTY XL2 model features an extra wide opening specifically designed for tying products from 1/2" to 2" in diameter. With up to 40 ties per minute, the ever adaptable XL2 seamlessly handles bag-in-box and flow-through packaging operations with ease.

XL2

Genuine Plas-Ties' Twist Tie Material required for optimal performance

BENEFITS

- :: Durable, All-Metal Frame
- :: Bundles up to 40 Ties / Minute
- :: Adjustable Tying Diameter
- :: Multi-Directional Orientation
- :: Production Counter
- :: UL Listed
- :: Made in the USA

OPTIONS:

- :: Side Mount
- :: 5 Twist
- :: Pedestal Stand

FEATURES:

XL2 SPECS	
Capacity	½" - 2"
Approx. tie length	3 ½" – 9 ½"
#of twists	2 1/2
Speed	Up to 40 Ties per minute
Spool size	24-gauge wire,single/dbl
	wire,
Power	5/32" or ¼" width
	120 VAC,60 HZ,2 AMPS
Weight (w/ brake & bench)	50 lbs.
Length	40"
Height	17 ½"
Width at Top	14"
Width (Front feet)	16"

Commercial-Grade: Tackles high production warehouses with minimal maintenance

Small Footprint: Standard model offers a small footprint, leaving more room for your workstations

High Reliability: Workhorse, proven to outperform manual labor

Optional Stand: Easily transforms the XL2 into a mobile workstation

Flexible Loaner Program - Machine is on loan while your unit is in for service - no downtime!

Domestic Inventory of Parts - Next Day Delivery Option available

On-going Tech Support: Free on-line manuals, video & phone support available

Factory Training Options: Customized to your needs and budget

Applications:

: Extension Cords/Cables : Wire Harness Assemblies : Thick Poly Bags : Telecommunication Cables

: Bag-in-Box Applications : Packaging Peanuts

: Hoses

14272 Chambers Rd Tustin, CA 92780 FAX: (714) 972-2978 (800) 854-0137 www.plasties.com info@plasties.com